

PENRITE OIL



PENRITE OIL COMPANY PTY. LTD. 3 CROSS STREET, EAST BRUNSWICK, VICTORIA.

ACN 005 001 525

P.O. BOX 140, BRUNSWICK, 3056. TELEPHONE: (03) 387 2633 FACSIMILE: (03) 387 9471.

PENRITE OIL RECOMMENDATION CHART FOR SS AND JAGUAR CARS

<u>YEAR / MODEL</u>		<u>ENGINE</u>	<u>GEARBOX</u>	<u>AXLE</u>		
To 1933 / SS1	5.6SV	HPR-30	Transoil 90	Transoil 140		
1934 - 1936						
SS1	5.6SV	HPR-30	Gear Oil 30	Transoil 140		
SS11	5.4SV	HPR-30	Gear Oil 30	Transoil 140		
SS90	5.6SV	HPR-30	Gear Oil 30	Transoil 140		
1936 - 1937						
1½ Litre Saloon	5.4SV	HPR-30	Gear Oil 30	Mild EP		
2½ Litre Saloon	5.6 OMV	HPR-30	Gear Oil 30	Mild EP		
2½ Litre 100	5.6 OMV	HPR-30	Gear Oil 30	Mild EP		
1938 - 1951					<u>ENV</u>	<u>SALISBURY</u>
1½ Litre Saloon	5.4 OMV	HPR-30	Gear Oil 30	Mild EP		Hypoid 85W/140
2½ / 3½	5.6 OMV	HPR-30	Gear Oil 30	Mild EP		
2½ / 3½ 100	5.6 OMV	HPR-30	Gear Oil 30	Mild EP		
MKV	5.6 OMV	HPR-30	Gear Oil 30	Mild EP		
XK 120, 140, 150		HPR-30	Gear Oil 30	Hypoid 85W/140		
All Models		(7.4 - 13.7)	(1.4)	(1.5 or 2.0)		
C Type		HPR-30 (10.8)	Gear Oil 30 (1.4)	Hypoid 85W/140 (1.7)		
D Type		HPR-30 (15.9)	Gear Oil 30 (1.4)	Hypoid 85W/140 (1.7)		
E Type		HPR-30 (8.6)	Gear Oil 30	Hypoid 85W/140 (1.6)		
		V-12 (10.8)	(1.4 or 1.7)	Powr - Lok Diff		
				Limslip 85W/140 (1.6)		
Saloons		HPR-30 (6.8)	Gear Oil 30	Hypoid 85W/140 (1.6)		
MK's VII, VIIM, VIII			(1.4)(2.3 with OD)	Hypoid 85W/140 (1.6)		
IX, X			Auto - ATF			



PENRITE OIL



PENRITE OIL COMPANY PTY. LTD. 3 CROSS STREET, EAST BRUNSWICK, VICTORIA.

ACN 005 001 525

P.O. BOX 140, BRUNSWICK, 3056. TELEPHONE: (03) 387 2633 FACSIMILE: (03) 387 9471.

2.4, 3.4, 3.8, MKI & II S Type 240 / 340 420 / Daimler Sovereign 420G	HPR-30 (6.8)	Gear Oil 30 (1.4) (2.3 with OD) Autos - ATF (8.6)	Hypoid 85W/140 (1.6) Powr-Lok Diff Limslip 85W/140 (1.6)
XJ6 Range	HPR-30 (8.2 or 8.0)	Gear Oil 30 (1.7, 2.0 or 2.6) Autos ATF (8.6)	Hypoid 85W/140 (1.6) for Powr - Lok use Limslip 85W/140 (1.6)
XJ12 Range	HPR-30 (10 or 9.2)	ATF (8.6)	Limslip 85W140 (1.6)
XJS Range	HPR-30 (8.5, 10.8 or 11.3)	Gear Oil 30 (2.4 or 1.4) Autos - ATF	Limslip 85W/140 (1.6)

ENGINE

- Oil recommendations assume engines in good run in condition
- Use Penrite Running In Oil for thorough piston Ring Bedding in all models
- For well used engines, use one grade heavier HPR-50 to improve oil consumption & high temperature oil pressure
- For long-distance competitions use Penrite 10/Tenths 15W/40 or 25W/60 Synthetic Oil

GEARBOX

- Gear Oil 30 is suitable for all 4 speed & overdrive boxes. Do not use EP gear oil in overdrives

AXLE

- Hypoid 80W/90 is available for very cold conditions
- Limslip oil is designed for friction-tyre limited slip differentials



PENRITE OIL COMPANY PTY. LTD. 3 CROSS STREET, EAST BRUNSWICK, VICTORIA.

ACN 005 001 525

P.O. BOX 140, BRUNSWICK, 3056. TELEPHONE: (03) 387 2633 FACSIMILE: (03) 387 9471.

GENERAL

- | | |
|-------------------------------|---|
| - Steering Box | Mild EP or where leaks are a problem, Steering Box Lube |
| - Carb Dashpots | SU Dash Pot Oil |
| - Water Pumps | use Penrite Water Pump grease |
| - Prop Shaft Joints | use graphite grease |
| - Grease Nipples | use graphite grease |
| - Oil Points | use engine oil |
| - Lever Arm Shock Absorbers | use shock oil 1 |
| - Vane type shock absorbers | Luvax tyre use Transoil 90 or 140 |
| - For long term engine lay up | use Penrite storage oil |
| - for engine build protection | use Penrite Camshaft assembly Lube |